



Product Service

CERTIFICATE

No. Z1A 090361 0047 Rev. 00

Holder of Certificate: **Kinnarps AB**

Industrigatan 1
521 88 Kinnarp
SWEDEN

Certification Mark:



Product:

**Office furniture/accessories
Sound absorption and screening
for use in offices or public areas**

Tested according to:

DIN EN 1023-1:1996
DIN EN 1023-2:2001
DIN EN 1023-3:2001
DGUV Grundsatz 315-410:2021
PPP 59041B:2022

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713339093

Valid until: 2030-04-21

Date, 2025-04-22

(Michael Weber)

CERTIFICATE

No. Z1A 090361 0047 Rev. 00

Model(s):

VIBE

**FREESTANDING PARTITION SCREEN FOCUS,
LINKABLE PARTITION SCREEN FOCUS,
ADD-ON PARTITION SCREEN FOCUS,
WALL-MOUNTED SCREEN FOCUS,
CEILING-SUSPENDED SCREEN FOCUS,
DESKTOP SCREEN LIGHT,
DESKTOP SCREEN FOCUS**

Parameters:

Vibe screens are available as freestanding partition screen, linkable partition screen, add-on partition screen, wall-mounted screen, ceiling-suspended screen and desktop screen.

The screens are fabric-covered with a zip in the lower edge and are sound-absorbent.

FREESTANDING PARTITION SCREEN FOCUS

Screen thickness: 40 mm

Width x Height: 765 x 1200 mm (VF812F), 765 x 1400 mm (VF814F),
865 x 1400 mm (VF914F), 965 x 1200 mm (VF1012F), 965 x 1400 mm (VF1014F),
1165 x 1200 mm (VF1212F), 1165 x 1400 mm (VF1214F), 1265 x 1200 mm (VF1314F),
1465 x 1200 mm (VF1512F), 1465 x 1400 mm (VF1514F), 1665 x 1200 mm (VF1712F),
1665 x 1400 mm (VF1714F), 1865 x 1400 mm (VF1914F)

Support foot: Metal support foot on glides (VMF), Metal legs high (VMLH)

Width x Height: 765 x 1600 mm (VF816F), 765 x 1800 mm (VF818F),
965 x 1600 mm (VF1016F), 965 x 1800 mm (VF1018F), 1165 x 1600 mm (VF1216F),
1165 x 1800 mm (VF1218F), 1465 x 1600 mm (VF1516F), 1465 x 1800 mm (VF1518F),
1665 x 1600 mm (VF1716F), 1665 x 1800 mm (VF1718F)

Support foot: Metal support foot on glides (VMF)

LINKABLE PARTITION SCREEN FOCUS

Screen thickness: 40 mm

Width x Height: 800 x 1200 mm (VF812T), 800 x 1400 mm (VF814T),
800 x 1600 mm (VF816T), 800 x 1800 mm (VF818T), 900 x 1400 mm (VF914T),
1000 x 1200 mm (VF1012T), 1000 x 1400 mm (VF1014T), 1000 x 1600 mm (VF1016T),
1000 x 1800 mm (VF1018T), 1200 x 1200 mm (VF1212T), 1200 x 1400 mm (VF1214T),
1200 x 1600 mm (VF1216T), 1200 x 1800 mm (VF1218T), 1300 x 1400 mm (VF1314T),
1500 x 1200 mm (VF1512T), 1500 x 1400 mm (VF1514T), 1500 x 1600 mm (VF1516T),
1500 x 1800 mm (VF1518T), 1700 x 1200 mm (VF1712T), 1700 x 1400 mm (VF1714T),
1700 x 1600 mm (VF1716T), 1700 x 1800 mm (VF1718T), 1900 x 1400 mm (VF1914T)

Support foot: Metal support foot on glides (VMF), Round metal support foot (VRMF)

CERTIFICATE

No. Z1A 090361 0047 Rev. 00

ADD-ON PARTITION SCREEN FOCUS

Screen thickness: 40 mm

Width x Height: 800 x 1200 mm (VF812TEX), 800 x 1400 mm (VF814TEX),
 800 x 1600 mm (VF816TEX), 800 x 1800 mm (VF818TEX), 900 x 1400 mm (VF914TEX),
 1000 x 1200 mm (VF1012TEX), 1000 x 1400 mm (VF1014TEX),
 1000 x 1600 mm (VF1016TEX), 1000 x 1800 mm (VF1018TEX),
 1200 x 1200 mm (VF1212TEX), 1200 x 1400 mm (VF1214TEX),
 1200 x 1600 mm (VF1216TEX), 1200 x 1800 mm (VF1218TEX),
 1300 x 1400 mm (VF1314TEX), 1500 x 1200 mm (VF1512TEX),
 1500 x 1400 mm (VF1514TEX), 1500 x 1600 mm (VF1516TEX),
 1500 x 1800 mm (VF1518TEX), 1700 x 1200 mm (VF1712TEX),
 1700 x 1400 mm (VF1714TEX), 1700 x 1600 mm (VF1716TEX),
 1700 x 1800 mm (VF1718TEX), 1900 x 1400 mm (VF1914TEX)

Support foot: Metal support foot on glides (VMF), Round metal support foot (VRMF)

WALL-MOUNTED SCREEN FOCUS

Screen thickness: 40 mm

Width x Height: 765 x 1400 mm (VF814W), 765 x 1600 mm (VF816W),
 765 x 1800 mm (VF818W), 1165 x 371 mm (VF124W), 1165 x 1000 mm (VF1210W),
 1165 x 1200 mm (VF1212W), 1165 x 1400 mm (VF1214W)

CEILING-SUSPENDED SCREEN FOCUS

Screen thickness: 40 mm

Width x Height: 1200 x 361 mm (VFH120L), 1400 x 361 mm (VFH140L),
 1600 x 361 mm (VFH160L), 1800 x 361 mm (VFH180L), 2000 x 361 mm (VFH200L),
 1200 x 640 mm (VFH120M), 1400 x 640 mm (VFH140M), 1600 x 640 mm (VFH160M),
 1800 x 640 mm (VFH180M), 2000 x 640 mm (VFH200M), 1200 x 800 mm (VFH120H),
 1400 x 640 mm (VFH140H), 1600 x 800 mm (VFH160H), 1800 x 800 mm (VFH180H),
 2000 x 800 mm (VFH200H), 765 x 1400 mm (VFH814), 765 x 1600 mm (VFH816H),
 1165 x 1000 mm (VFH1210), 1165 x 1200 mm (VFH1212), 1165 x 1400 mm (VFH1214)



Product Service

CERTIFICATE

No. Z1A 090361 0047 Rev. 00

DESKTOP SCREEN LIGHT

Screen thickness: 20 mm

ONTOP

For mounting on desks by using bracket, positioned above desktop

Width x Height: 1200 x 361 mm (VLD120T), 1400 x 361 mm (VLD140T),
1600 x 361 mm (VLD160T), 1800 x 361 mm (VLD180T), 2000 x 361 mm (VLD200T)

FLYBY

For mounting on desks by using bracket, positioned in front of desktop

Width x Height: 700 x 650 mm (VLD70F), 1200 x 650 mm (VLD120F),
1400 x 650 mm (VLD140F), 1600 x 650 mm (VLD160F), 1800 x 650 mm (VLD180F),
2000 x 650 mm (VLD200F)

For mounting on desks by using bracket, side screen with chamfered edge

Width x Height: 860/781 x 650 mm (VLD86FCL), 860/781 x 650 mm (VLD86FCR),
960/881 x 650 mm (VLD96FCL), 960/881 x 650 mm (VLD96FCR)

For mounting on desks by using bracket, side screen with straight edge

Width x Height: 620 x 650 mm (VLD62F), 720 x 650 mm (VLD72F),
820 x 650 mm (VLD82F), 920 x 650 mm (VLD92F)

For mounting on desks by using bracket, divider with chamfered edge

Width x Height: 840/795 x 371 mm (VLD84DC), 940/895 x 371 mm (VLD94DC)

CERTIFICATE

No. Z1A 090361 0047 Rev. 00

DESKTOP SCREEN FOCUS

Screen thickness: 40 mm

ONTOP

For mounting on desks by using bracket, positioned above desktop

Width x Height: 1200 x 361 mm (VFD120OT), 1400 x 361 mm (VFD140OT),
1600 x 361 mm (VFD160OT), 1800 x 361 mm (VFD180OT),
2000 x 361 mm (VFD200OT)

FLYBY

For mounting on desks by using bracket, positioned in front of desktop

Width x Height: 700 x 650 mm (VFD70F), 1200 x 650 mm (VFD120F),
1400 x 650 mm (VFD140F), 1600 x 650 mm (VFD160F), 1800 x 650 mm (VFD180F),
2000 x 650 mm (VFD200F), 700 x 800 mm (VFD70FH), 1200 x 800 mm (VFD120FH),
1400 x 800 mm (VFD140FH), 1600 x 800 mm (VFD160FH),
1800 x 800 mm (VFD180FH), 2000 x 800 mm (VFD200FH)

For mounting on desks by using bracket, side screen with chamfered edge

Width x Height: 870/791 x 650 mm (VFD87FCL), 870/791 x 650 mm (VFD87FCR),
970/891 x 650 mm (VFD97FCL), 970/891 x 650 mm (VFD97FCR),
1700/1504 x 650 mm (VFD170FC), 870/772 x 800 mm (VFD87FHCL),
870/772 x 800 mm (VFD87FHCR), 1700/1504 x 800 mm (VFD170FHC)

For mounting on desks by using bracket, side screen with straight edge

Width x Height: 640 x 650 mm (VFD64F), 740 x 650 mm (VFD74F),
840 x 650 mm (VFD84F), 940 x 650 mm (VFD94F), 640 x 800 mm (VFD64FH),
740 x 800 mm (VFD74FH), 840 x 800 mm (VFD84FH), 940 x 800 mm (VFD94FH)

For mounting on desks by using bracket, divider with chamfered edge

Width x Height: 920/875 x 371 mm (VFD92DC), 820/775 x 371 mm (VFD82DC)